




IC30 Proximity Card Reader

Model	IC 30
Power Supply	12vDC 1A, AC Adapter included
Image	
Power	<3V
Temperature	0°C ~ +45°C
Computer & OS Supported	300MHz+CPU, 128 MB+ RAM with Windows XP, Vista
Humidity	20%- 80% RH
LCD Display	128x68 Graphics Blue LCD Display with Backlight
Access control	External Relay Box required (Optional)
LCD Language	English
Keypad	16 Keys
Accessories and Packaging list	AC Adapter, Mounting Bracket & Screws, CD, Cables, Manuals
Voice	Integrated Human Voice and Buzzer
Real Time Clock	Yes
Central Processing Unit	ARM9 Dual core, Low power consumption
Storage	4M
Card Storage Capacity	10,000
Password Storage Capacity	10,000
Transaction Record	240,000
RS232	Yes
USB	Yes
TCI/IP	Yes
Communication Baud Rate	9600 19200 38400 57600 115200
Card Sensor Type	Proximity
Identification Speed	<0.85
Sensor Distance	6-8 cm
Identification Model	Card Work Id + Password
Ring inside	Yes
Battery Backup	Yes

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata- 700 001, INDIA

Phone : 91-33-2242-4094, 2231-8007 • Telefax : 91-33-2242-0492

E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com