

1/4 INCH COLOR CAMERA

1/4 INCH COLOR CAMERA



PICK UP DEVICE:	1/4 INCH SONY CCD IMAGE SENSOR
PICTURE ELEMENTS:	510 x 492 (NTSC) 500 x 582(PAL)
WHITE BALANCE:	MCT-AWB (MULTI-COLOR TEMPERATURE AUTO WHITE BALANCE)
GAIN CONTROL:	AUTO
ELECTRONIC SHUTTER:	NTSC: 1/60s to 1/120,000s, PAL: 1/50s to 1/120,000s
POWER SOURCE:	DC12V, AC 24V, 110V, 230V

1/4 INCH COLOR DOME CAMERA



MODEL NO.:	C5833-62A1 (NTSC) / C5834-62A1 (PAL)	
PICK-UP SIZE:	1/4 INCH SONY CCD IMAGE SENSOR (INTER LINE)	
SIGNAL MODE:	NTSC	PAL
VERTICAL FREQUENCY:	59.94 Hz	50 Hz
PICTURE ELEMENTS:	510 x 492 (NTSC)	500 x 582(PAL)
HORIZONTAL FREQUENCY:	15.734 KHz	15.625 KHz
SYNC. MODE:	INTERNAL	
SCANNING SYSTEM:	2:1 INTERLACE	
MINIMUM ILLUMINATION:	0.5 LUX, F=1.2	
HORIZONTAL RESOLUTION:	380 TV LINES	
AUTO SHUTTER FUNCTION:	AUTO	
S/N RATIO:	MORE THAN 48dB (AGC OFF)	
GAMMA CHARACTERISTIC:	r = 0.45	
GAIN CONTROL:	AUTO	
BLACK LIGHT COMPENSATION:	AUTO	
WHITE BALANCE:	MCT-AWB (MULTI-COLOR TEMPERATURE AUTO WHITE BALANCE)	
AUTO ELECTRONIC SHUTTER:	NTSC: 1/60s to 1/100,000s, PAL: 1/50s TO 1/110,000s	
VIDEO OUTPUT:	COMPOSITE 1.0 Vp-p AT 75 OHMS	
POWER REQUIREMENT:	DC12V	

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
 Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
 E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner