



Standalone DVR

Hikvision net DVR uses the Real Time OS and embedded MCU. It has both features of digital video recorder (DVR) and digital video server (DVS). It can work stand-alone or be used to build a powerful network, widely used in surveillance fields.

Model Name

DS-8000HCI Series DVRs



Front Panel



DS-8016HCI Rear Panel

DS-8000HCI series DVRs include following models:

DS-8004HCI: 4-ch video input and 4-ch audio input. The 1st channel can max support **4CIF** compression resolution real time, and other channels can only max support **CIF** resolution real time. It has 4 IDE interfaces.

DS-8008HCI: 8-ch video input and 8-ch audio input. The 1st and 5th channels can max support **4CIF** compression resolution real time, and other channels can only max support **CIF** resolution real time. It has 4 IDE interfaces.

DS-8012HCI: 12-ch video input and 12-ch audio input. The 1st, 5th and 9th channels can max support **4CIF** compression resolution real time, and other channels can only max support **CIF** resolution real time. It has 4 IDE interfaces.

DS-8016HCI: 16-ch video input and 16-ch audio input. The 1st, 5th, 9th and 13th channels can max support **4CIF** compression resolution real time, and other channels can only max support **CIF** resolution real time. It has 4 IDE interfaces.

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA

Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492

E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner