

High Resolution 30X Speed Dome Camera

SPD-3000



Specifications

Mode	SPD-3000N	SPD-3000P
Power Source	24V AC	
Power Consumption	8Watts in standing by 13Watts in operating	
Image Pick-up Device	1/4" Super HAD CCD	
Total Pixels	811(H) x 508(V)	795(H) x 596(V)
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Scanning System	2 : 1 Interlace, 625 Lines / 60 Fields / 30 Frames	2 : 1 Interlace, 625 Lines / 50 Fields / 25 Frames
Synchronization	External selectable (AC line lock)	
Scanning Frequency	15.734KHz(H) / 59.94Hz(V)	15.625KHz(H) / 50.00Hz(V)
Resolution	Color : 520TV lines (Min.) / B/W : 570TV lines (Min.)	
Video Output	1.0p-p / 75Ω	
S / N Ratio	More than 50dB (AGC off)	
Min. Illumination	0.7Lux @ F1.6 (Normal color mode)	
	0.1 Lux @ F1.6 (B/W mode)	
	0.005Lux @ F1.6 (Sens-up mode)	
Day & Night	Auto / Color / B/W (ICR filter change)	
Electronic Shutter Speed	Auto / Manual selectable (1/60 ~ 1/120,000)	Auto / Manual selectable (1/50 ~ 1/120,000)
Slow-shutter	On (2X ~ 128X fields) / Off selectable	
White Balance	ATW / AWC / Manual selectable	
Gain Control	Auto / Manual selectable	
OSD	On / Off selectable	
DIS(Digital Imager Stabilizer)	On / Off selectable	
Digital Zoom	2X ~ 10X (Total 300X zoom)	
Zoom Ratio	f3.3 ~ 99.0mm (30X)	
Multiple Protocols	PELCO-D, Panasonic, Vicon, Samsung Electronics	
Serial Communication	RS-485, RS-422, RS-232C	
Min. Focus Distance	1.2m	
Max. Zoom Speed	5.2sec	5.4sec
Pan Rotation Angle	360° Endless	
Pan Speed	240°/sec (64 step)	
Tilt Rotation Angle	-4° to 184°	
Tilt Speed	240°/sec (64 step)	
Angle Field of View	H : 58.17°(Wide) to 2.2°(Tele) / V : 44.76°(Wide) to 1.76°(Tele)	
Privacy Function	On / Off Selectable (4 Programmable zone)	
Pre-set	128 preset (Straight)	
Digital Flip	On / Off selectable	
Operating	Temperature	-10°C ~ +50°C
	Humidity	20% ~ 60% RH
Dimensions	Ø155(W) x 243.4(H)mm	
Weight	Approx. 2.0kg	

Dimensions

Unit : mm



Controller (Option)




Accessories & Dimensions (For SPD-3300/3000/2300)

Unit : mm



For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA

Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492

E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

CS # 85

Our Partner