

Electronic Locking Systems & Accessories

Electric Lock Series

Suitable For Security or Access Control System



- eLock-600, eLock-600L EM Lock**
- 600LBS holding force
 - 12V/ 24V operation
 - Current draw 500mA/ 250mA
 - Fail-Safe Type
 - LED, magnetic Bond Sensor, NO, NC relay (eLock-600L)
 - Dimension: 250mm(L) X 41mm(W) X 26mm(D)



- eLock-1200, eLock-1200L EM Lock**
- 1200LBS holding force
 - 12V/ 24V operation
 - Current draw 500mA/ 250mA
 - Fail-Safe Type
 - LED, magnetic Bond Sensor, NO, NC relay (eLock-1200L)
 - Dimension: 265mm(L) X 66mm(W) X 40mm(D)



- eLock-S200 Strike Lock**
- 12V operation
 - operation current 360mA
 - Fail-Safe/ Fail-Secure Type
 - Dimension: 160mm(L) X 25mm(W) X 31mm(D)



- eLock-S220 Strike Lock**
- 12V operation
 - Operation current 360mA
 - Fail-Safe/ Fail-Secure Type
 - Dimension: 124mm(L) X 32mm(W) X 38mm(D)



- eLock-B100 Bolt Action Lock**
- 12V operation
 - Operation current 900mA
 - Holding current 350mA
 - Fail-Safe Type
 - Operation Delay Time: 0sec, 2.5sec, 5sec, 9sec
 - Door Sensor (NC & NO)
 - Built-in Delayed Egress, Control Point
 - Dimension:
 - Face Plate: 200mm(L) X 32mm(W) X 40mm(D)
 - Strike Plate: 90mm(L) X 26mm(W) X 2mm(D)
 - Bolt: Stainless Steel 15.5 Diameter, 16mm Throw

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner

Electronic Locking Systems & Accessories



EL-BK-G200
Frameless Glass Door Housing

- To be used with elock-B100 Bolt Action Lock
- Suitable for 90° or 180° door
- Sturdy built for durability
- Simple installation without drilling any holes
- To be used with EL-BK-G201 glass holder
- Dimensions:
230mm(L) X 45mm(W) X 46mm(D)
- Weight: 590g

EL-BK-G201
Glass Holder

- To be used with EL-BK-G200 to install elock-B100 Bolt Action lock
- Suitable for glass (thickness of 9mm-12mm)
- Stainless steel built for durability
- Rubber plate and steel plate for strong holding
- Dimensions of large glass holder:
195mm(L) X 46mm(W) X 16mm(D)
- Dimensions of small glass holder:
120.5mm(L) X 46mm(W) X 16mm(D)
- Weight: 1000g



EL-830P
Concealed Magnetic Contact

- Dimension: 20 (L) x 5 (D)

EL-810P
Magnetic Contact

- Dimension: 50 (L) x 10 (W) x 10(D)



EL-KS1
Key Switch

- 2 position Removable Key, single pole
- Flush Stainless Steel face plate
- Lock housing : Zinc Alloy Die-Casted, chrome plated
- Cylinder : 7 pin constructed, Zinc Alloy Die-casted
- Tubular key Nickel plated
- Contact Rating : 4A 125VAC, 2A 250VAC
- CE approved


EL-EB1
Exit Button

- Flush Stainless Steel face plate
- Narrow style
- Button housing : Zinc Alloy Die-Casted, chrome plated
- NO, C contacts
- Contact Rating : 4A 125VAC, 2A 250VAC
- CE approved

EL-EB2
Illuminated, Indicator Switch

- Illuminated switch
- Narrow style
- Single pole, double throw, double break switching mechanism
- Contact Rating : 4A 125VAC, 2A 250VAC
- Illumination lamp - 60V/1.2W Max.
- CE approved

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner