

High Resolution Day & Night 3-Axis Dome Camera


SID-450



Specifications

Model	SID-450N	SID-450P
Power Source	12V DC 10% compatible	
Power Consumption	Max. 2.5W	
Total Pixels	811(H) x 508(V)	795(H) x 596(V)
Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
Image Pick-up Device	1/3" Super HAD CCD	
Scanning System	2 : 1 Interlace	
Scanning Frequency	15.734KHz(H) / 59.94Hz(V)	15.625KHz(H) / 50.00Hz(V)
Synchronization	Internal / Line lock	
Resolution	530TV lines	
Video Output	1.0Vp-p / 75Ω (Video : 0.714Vp-p, Sync : 0.286Vp-p)	
S/N (Y signal)	50dB (AGC off, Weight on)	
Min. Illumination	0.3Lux @ F1.2, 0.002Lux @ F1.2 (Sens-up, 128X)	
Day & Night	On / Auto selectable	
BLC	Low / Middle / High / Off selectable	
Gain Control	Low / Middle / High / Off selectable	
SSNR	Low / Middle / High / Off selectable	
White Balance	ATW / AWC / Manual selectable (1800°K ~ 10,500°K)	
Electronic Shutter	Fixed (1/60 or Flickerless mode)	Fixed (1/50 or Flickerless mode)
Sens-up	Auto / Off (2X ~ 128X)	
OSD	Built-in	
Motion Detection	On / Off (4 Programmable zone, Screen display)	
Mirror	On / Off	
Privacy Function	On / Off (4 Programmable zone)	
Sharpness	On / Off (Level adjustable)	
Focal Length	3.0mm ~ 9.0mm	
Max. Aperture Ratio	1 : 1.2 ~ 2.1	
Viewing Angle	H : 31.8° (Tele) ~ 90.0° (Wide) / V : 23.9° (Tele) ~ 66.2° (Wide)	
Monitoring Angle	Pan	-175° ~ 175°
	Tilt	-80° ~ 80°
	Rotation	-175° ~ 175°
Operating	Temperature	-10°C ~ +50°C
	Humidity	30% ~ 80% RH
Dimension	130(ø) x 100(H)mm	
Weight	570g	

Dimensions



ø130



ø130

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
 Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
 E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

CS # 83

Our Partner