

# PP-5707i Access Controller

## Economical Access Controller / Card Reader

### Features:

- ① Support contactless thick, thin card (credit card size and easy for color printing) and keyfob.
- ① With nonvolatile memory for 2,000 cards and 2,000 events
- ① Card can be added/deleted/inquired in single/ block of range or by read & learning by manual operation or via PC.
- ① System parameters and personal maps editing with keypad by master card also can be uploaded / downloaded via on-line PC.
- ① Multiple networking system can be configured to control up to 160 doors with supports of PCK106 multi-channel controller. Thousands access controllers system can be easily configured thru PC-T100 (TCP/IP converter) for Web based networking .
- ① Auto power reset with watchdog timer and low power RTC design, data retention for 10 years while power failure.
- ① Single door controller
- ① Membrane keypad
- ① RS485 communication
- ① 2000 users
- ① 2000 transactions
- ① Port for exit reader
- ① Dual functionality (Card reading while downloading is in process)
- ① 4 digit card number verification
- ① Tamper switch output
- ① 115kbps data speed
- ① Brand new case, sleek new design
- ① CE certified
- ① Stand alone and Networkable
- ① Economical price



### Specifications:

Model No.	PP-5707i
Card type	EM
Read range	3-15 cm
Frequency / Modulation	125KHz / ASK
On-line Interface	RS-485. Web-based networking, 10/100Mbps auto-sensing (TCP/IP converter PC-T100)
Baud rate	300-115,200 bps, N,8,1 (default 115kbps)
Card holders/events	2,000 card holders / 2,000 events
Inputs	3 inputs for external reader, push button, door monitoring
Outputs	2 outputs for door release, tamper & switch
Mounting	Surface mount with waterproof
Enclosure material / color	ABS / white
Keypad	4 x 3 numeric keypad, waterproof
Indicators	Bicolor (red/green) and amber LEDs, multi-tone buzzer
Power supply	12V DC, 150 mA(Linear power supply recommended)
Operation temperature	0°C ~ 55°C
Humidity	10%~90% RH, Non condensation
Weight	340g±5%

Represented by:

For Single Point Solution from Designing to After Sales & Service. Please contact



## COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA  
 Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492  
 E-mail : [info@comptronicsolutions.com](mailto:info@comptronicsolutions.com) • Website : [www.comptronicsolutions.com](http://www.comptronicsolutions.com)

Our Partner