

PP-6707i Access Controller

**Intelligent 3 in 1 design for proximity
Card reader / Access Controller / Time & Attendance**

Features:

- 1 Proximity Reader / Access Controller / Time & Attendance 3 in 1 design, supports stand-alone or intelligent PC on/off-line operation.
- 2 Built-in reader and provides a standard Wiegand input for external reader with anti-pass back function, also comes with 24/36/48 hours anti-pass back reset function.
- 3 Support contactless thick, thin card (credit card size and easy for color printing) and keyfob.
- 4 With nonvolatile memory for 2,000 cards and 1,800 events
- 5 Operation modes: 1. card only 2. card and PIN 3. keying only (by card number and PIN) 4. auto operation mode by time zones 5. personalized operation mode (optional) 6. auto free access
- 6 Card can be added/deleted/inquired in single/ block of range or by read & learning by manual operation or via PC.
- 7 System parameters and personal maps editing with keypad by master card or thru 6 digits master PIN, also can be uploaded / downloaded via on-line PC.
- 8 Multiple networking system can be configured to control up to 160 doors with supports of PCK106 multi-channel convertor. Thousands access controllers system can be easily configured thru PC-T100 (TCP/IP converter) for Web based networking .
- 9 168 time alarm for bell schedules and 96 holiday schedules.
- 10 Keypad lockable by master PIN and selectable Anti-duress code function to enhance security.
- 11 Check repeat reading function to prevent repeating reading within 1-9 minutes.
- 12 Auto power reset with watchdog timer and low power RTC design, data retention for 10 years while power failure.




Specifications:

Model No.	PP-6707i
Card type	EM
Read range	5-20 cm
Frequency / Modulation	125KHz / ASK
On-line Interface	RS-232C or RS-422 or RS-485. Web-based networking, 10/100Mbps auto-sensing (TCP/IP converter PC-T100)
Baud rate	300-115,200 bps, N,8,1 (default 115kbps)
Card holders/events	2,000 card holders / 1,800 events
Time zone	8 personal time zones, 8 time zones for auto duty mode 8 time zones for auto operation mode
Inputs	3 inputs for external reader, push button, door monitoring
Outputs	5 outputs for door release, alarm, printer output, tamper switch, and door bell
Mounting	Surface mount with waterproof
Enclosure material / color	ABS / dark grey
Keypad	4 x 3 numeric keypad, waterproof
Indicators	Bicolor (red/green) and amber LEDs, multi-tone buzzer
Power supply	12V DC, 150 mA (Linear power supply recommended)
Operation temperature	0°C ~ 55°C
Humidity	10%~90% RH, Non condensation
Dimensions	137(L) x 85(W) x 25(H) mm / 5.39(L) x 3.35(W) x 1.14(H) inch
Weight	340g±5%



For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner