

Full Height Turnstile Gate



The highest quality industrial type weatherproof security gate. Heaviest of its class and by far the most with the longest service life. Features that assure the highest security and dependability including a robust construction. Controls can be integrated into any automated security system. Automatically assure passage in the unlocked direction only. The unquestioned leader in outdoor industrial security.

Arms: Hot dip galvanized steel tubing, wall thickness of 0.105" and 1.31" O.D. Arm Ends Spun close heat and pressure, for a smooth safe finish.

Standard Equipment:

- All bearings are permanently lubricated.
- Mechanically fastened arms (stronger than welded) and easily replaced if damaged
- All locking components are hardened steel.
- Delrin main indexing cam provides years of maintenance free reliability.
- Bronze oil-impregnated bushings for low maintenance.
- Adjustable hydraulic speed control.
- Hot dipped galvanized finish.

Standard Electric Components:

- 24-volt operating system.
- Adjustable timer.
- Fail lock or fail-safe.
- Heavy-duty pull type solenoid.
- Dry contact relay.
- 12 volt or 24 volt pulse relay.

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner

Tripod Turnstile Gate



Tripod Turnstile gate:

Heavy-duty electronically controlled turnstile can be equipped for automatic revenue collection. Uniquely upgradeable so that the turnstiles will remain for decades as revenue systems are changed. Corrosion resistant. High security vault. Large captured ticket capacity. Extremely fast. Exceptional maintenance. Extremely long service life. Designed for the look of modern automatic fare collection. Three rotor sections provide a comfortable passage while still maintaining high security performance. Available with mechanical or electrical operation, in either one or two way operation, with any comb fall lock or fall secure.

Standard Equipment:

- All bearings are permanently lubricated.
- Mechanically fastened arms (stronger than welded) and easily replaced if damaged
- All locking components are hardened steel.

ped galvanized finish.

Standard Electric Components:

- 24-volt operating system.
- Adjustable timer.
- Fall lock or fall-safe.
- Heavy-duty pull type solenoid.
- Dry contact relay.
- 12 volt or 24 volt pulse relay.

For Single Point Solution from Designing to After Sales & Service. Please contact



COMPTRONIC SOLUTIONS

14/2, Old China Bazar Street, 3rd Floor, Suite No. 202, Kolkata - 700 001, INDIA
Phone : 91-33-2242-4094 / 2231-8007 • Telefax : 91-33-2242-0492
E-mail : info@comptronicsolutions.com • Website : www.comptronicsolutions.com

Our Partner